

Ventilation button



Performance features

- » For controlling ventilation drives
- » Self-explanatory symbols
- » Versions for flush-mounted and surface-mounted installation and for moisture-prone areas

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U 63.701.29



Ventilation button

- » For controlling a ventilation group
- » Ventilation "OPEN-STOP-CLOSED" via double button with 2 unlocked normally open contacts
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H x (D) in mm	80 x 80
Weight	0.15 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-SD 63.701.35



Ventilation button

- » For controlling a ventilation group
- » Ventilation "OPEN-STOP-CLOSED" via double button with 2 unlocked normally open contacts
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H x (D) in mm	80 x 80
Weight	0.15 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-W 63.701.31



Ventilation button

- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H x (D) in mm	80 x 80
Weight	0.30 kg

Type	Art. No.	Description	Technical data												
LT 84-U-V	63.701.30	Ventilation button <ul style="list-style-type: none"> » For controlling a 230 V AC ventilation group » Ventilation "OPEN-STOP-CLOSED" via double button; buttons mechanically interlocked; "STOP" by releasing the button » For installing in 55 mm flush-mounted socket (not included) 	<table border="1"> <tr> <td>Input voltage</td> <td>230 V AC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>80 x 80</td> </tr> <tr> <td>Weight</td> <td>0.30 kg</td> </tr> </table>	Input voltage	230 V AC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H x (D) in mm	80 x 80	Weight	0.30 kg
Input voltage	230 V AC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H x (D) in mm	80 x 80														
Weight	0.30 kg														



Type	Art. No.	Description	Technical data												
SLT 42U	30.401.10	Key vent button <ul style="list-style-type: none"> » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels » Function: Ventilation "OPEN-CLOSED" via key operated changeover contact » For installing in deep 55 mm flush-mounted sockets (not included) » Profile semi-cylinder not included in scope of supply 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>80 x 80</td> </tr> <tr> <td>Weight</td> <td>0.15 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H x (D) in mm	80 x 80	Weight	0.15 kg
Input voltage	24 V DC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H x (D) in mm	80 x 80														
Weight	0.15 kg														



Type	Art. No.	Description	Technical data												
SLT 42U-SD	30.400.50	Key vent button <ul style="list-style-type: none"> » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels » Function: Ventilation "OPEN-CLOSED" via key operated changeover contact » For installing in deep 55 mm flush-mounted sockets (not included) » Profile semi-cylinder not included in scope of supply 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>80 x 80</td> </tr> <tr> <td>Weight</td> <td>0.15 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H x (D) in mm	80 x 80	Weight	0.15 kg
Input voltage	24 V DC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H x (D) in mm	80 x 80														
Weight	0.15 kg														



Type	Art. No.	Description	Technical data												
SLT 42A	30.400.30	<p>Key vent button</p> <ul style="list-style-type: none"> » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels » Function: Ventilation "OPEN-CLOSED" via key operated changeover contact » Profile semi-cylinder not included in scope of supply 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 54</td> </tr> <tr> <td>Housing</td> <td>Aluminium</td> </tr> <tr> <td>Colour</td> <td>Light grey</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>70 x 90 x 65</td> </tr> <tr> <td>Weight</td> <td>0.45 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 54	Housing	Aluminium	Colour	Light grey	W x H x (D) in mm	70 x 90 x 65	Weight	0.45 kg
Input voltage	24 V DC														
Type of protection	IP 54														
Housing	Aluminium														
Colour	Light grey														
W x H x (D) in mm	70 x 90 x 65														
Weight	0.45 kg														



Type	Art. No.	Description	Technical data												
SLT 42A-SD	30.400.40	<p>Key vent button</p> <ul style="list-style-type: none"> » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels » Function: Ventilation "OPEN-CLOSED" via key operated changeover contact » Profile semi-cylinder not included in scope of supply 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 54</td> </tr> <tr> <td>Housing</td> <td>Aluminium</td> </tr> <tr> <td>Colour</td> <td>Light grey</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>70 x 90 x 65</td> </tr> <tr> <td>Weight</td> <td>0.45 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 54	Housing	Aluminium	Colour	Light grey	W x H x (D) in mm	70 x 90 x 65	Weight	0.45 kg
Input voltage	24 V DC														
Type of protection	IP 54														
Housing	Aluminium														
Colour	Light grey														
W x H x (D) in mm	70 x 90 x 65														
Weight	0.45 kg														



Type	Art. No.	Description	Technical data												
LT 84-A	63.701.36	<p>Ventilation button</p> <ul style="list-style-type: none"> » For controlling a ventilation group » Ventilation "OPEN-STOP-CLOSED" via double button with 2 unlocked normally open contacts 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 55</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>Light grey</td> </tr> <tr> <td>W x H x (D) in mm</td> <td>70 x 70 x 45</td> </tr> <tr> <td>Weight</td> <td>0.20 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 55	Housing	Plastic	Colour	Light grey	W x H x (D) in mm	70 x 70 x 45	Weight	0.20 kg
Input voltage	24 V DC														
Type of protection	IP 55														
Housing	Plastic														
Colour	Light grey														
W x H x (D) in mm	70 x 70 x 45														
Weight	0.20 kg														



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

AP-LT 63.701.33



Surface-mounted housing, single

» For holding a key vent button or vent button for surface-mounted installation

Housing	Plastic
Colour	White
W x H x (D) in mm	80 x 80 x 35
Weight	0.10 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

AP2-LT 63.701.34



Surface-mounted housing, double

» For holding a key vent button or vent button for surface-mounted installation

Housing	Plastic
Colour	White
W x H x (D) in mm	150 x 80 x 35
Weight	0.20 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-R2 63.701.32



Double frame

» For combining two key vent button or vent button in flush-mounted installation

Housing	Plastic
Colour	White
W x H x (D) in mm	150 x 80
Weight	0.10 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

PHZ 28

70.600.53

Profile semi-cylinder

» For key vent button (SLT)

Weight

0.15 kg

» Including 3 keys

